

**HCS-3300 Series with USB option**

Laboratory Grade & High RFI Immunity Switched Mode Power Supply



USB option 



**Description**

This series of high graded SMPS is designed for a wide range of applications in telecommunications, industry and research. The high efficiency circuit design allows all units to have small form factor with low profile and small footprint. The intelligent fan speed control checks the fan at power on and then adapts the speed to ensure a quiet and safe operation of the power supply at different ambient temperatures and power output levels. The dual action (coarse & fine set) control knobs make tuning the voltage and current level ever so smooth, precise and fast, due to the rotary encoder and microprocessor control. Setting the current limit can be performed with open circuit outputs. The isolated ground construction allows parallel and series connection of power supplies with ease and safety. The three user defined presets of voltage and current limiting levels facilitate quick access to frequently used VI settings. The full analogue remote control functionality (with optional USB control) offers a wide range of applications in R&D, Production Product Evaluation or QC testing and automated test equipment.

**Features**

- Rotary Encoder Controls with coarse and fine tuning
- 3 user defined Voltage and Current presets
- Full Remote Control of V, I and output on-off
- High RFI immunity and excellent EMI
- Isolated ground, Active PFC and high efficiency
- Intelligent fan control from zero to full speed
- Over load, Over Temperature and Tracking Over Voltage protection
- USB option with repeatable 20 x V, I, time step sequence software with V, I vs. time data logging capability. Labview driver and example programs in VisualBasic and VBA for Word and Excel are provided. **New! Android & iPad Apps!**

**Specifications**

Models	HCS-3300	HCS-3302	HCS-3304
<b>Output</b>			
Variable Output Voltage	1~16VDC	1~32VDC	1~60VDC
Variable Output Current	0~30A	0~15A	0~8A
<b>Voltage Regulation</b>			
Load (10~100% Load)	50mV		
Line (170~264VAC Variation)	20mV		
<b>Current Regulation</b>			
Load (10~90% Rated Voltage)	150mA	100mA	100mA
Line (170~264VAC Variation)	50mA		
<b>Ripple &amp; Noise</b>			
Ripple & Noise (rms) Voltage	5mV	5mV	5mV
Ripple & Noise (peak-peak) Voltage	50mV	50mV	100mV
Switching Frequency	65~85kHz	75~95kHz	65~85kHz
Tracking Over Voltage Protection	O/P 1~5V: set voltage + 2V O/P 5~15V: set voltage + 3V	O/P 1~5V: set voltage + 2V O/P 5~20V: set voltage + 3V O/P 20~30V: set voltage + 4V	O/P 1~5V: set voltage + 2V O/P 5~20V: set voltage + 3V O/P 20~60V: set voltage + 4V
<b>Meter Type &amp; Accuracy</b>			
Voltage Meter	3 Digit LED Display $\pm(0.2\% + 3 \text{ counts})$		
Current Meter	3 Digit LED Display $\pm(0.2\% + 3 \text{ counts})$		
Input Voltage	200~240VAC 50/60Hz		
Full Load Input Current	2.4A	2.4A	2.4A
Efficiency	85.5%	86.5%	87%
Power Factor Control	Power factor correction >0.95 at optimal load		
Cooling Method	Thermostatic Control Fan from Zero to full speed		
Protection	Overload, Short Circuit by Constant Current limiting, Output Tracking Over Voltage, Over Temperature Protection		
Special Features	3 User defined V, I presets, Remote control V, I and output on-off and USB option (HCS-330x-USB)		
Approvals	CE EMC: EN55011, EN55022 LVD: EN60950, EN61010		
Dimensions (WxHxD)	200x90x215mm 7.9x3.5x8.5in		
Weight	2.7kg 6lb (3.3kg 7.3lb in carton 33x26x14cm)		

- All values are based on the Standard ambient Temperature 25°C and Pressure 0.1Mpa.
- SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE