

HCS-3600AHR Series

900W Reversible Polarity Plating Rectifier with Amp-Hour Meter



Description

This series of power supplies are designed for the electrochemical surface treatment industry. This 900W switched mode DC regulated power supply is designed for applications which require frequent reverse polarity operations and an Amp-Hour display. Two sets of output terminals are provided, the main output is not reversible whilst the other set can be reversed in polarity using a Reversing Switch. In the OFF position the voltage and current may be set. When set to the reverse polarity a buzzer sounds to warn the user. Ideal features for use in brush electro-plating applications. NEW! Computer control allows the display of V+I data for record keeping and for programming of slow pulse waveforms and ramp times to improve anodizing and other processes. For information on brush plating services... see: www.dalic.com.au

Features

- Designed for Electrochemical treatment industry
- Reversible Polarity Output with OFF position
- Precision 6 digit Amp-Hour meter with Reset
- Constant voltage & current adjustment
- Rotary Encoder Controls with course & fine tuning
- Floating Ground design
- Over Temperature Protection
- Over load and short-circuit Protection
- Over Voltage Protection
- Variable speed thermally controlled fan
- High RFI stability
- Active Power Factor Correction > 0.95
- Housing is available in standard bench top or 19 inch rack mount design
- USB control & data logging capability included

Specifications

Models	HCS-3600AHR	HCS-3602AHR	HCS-3604AHR
Variable Output Voltage	1~16VDC	1~32VDC	1~60VDC
Variable Output Current	0~60A	0~30A	0~15A
Ripple & Noise (at Main Terminals)	5mVrms 50mVp-p		
Voltage Load Regulation (10~100% load at Main Terminals)	50mV		
Voltage Line Regulation (170~264VAC variation)	20mV		
Current Load Regulation (10~90% Rated Voltage)	200mA	150mA	100mA
Current Line Regulation (170~264VAC variation)	50mA		
Input Voltage	200~240VAC 50/60Hz		
Efficiency	86.5%	90%	90%
Power Factor	Power factor correction >0.95 at optimal load		
Voltage Meter	3 digit LED Display ±0.2% + 3 counts		
Current Meter	3 digit LED Display ±0.2% + 3 counts		
Amp-Hour Meter	6 digit LED Display "999.999" ±1.0% accuracy		
Cooling System	Variable speed thermally control fan (from 0 to full speed)		
Protection	Over Temperature, Short Circuit, Tracking Over Voltage Protection		
Dimensions (WxHxD)	430x95x280mm 17x3.75x11in (excludes knobs & terminals)		
Weight	6.8kg 15lb		
Special Features	Reverse Polarity Switch with OFF position, AH Meter with reset		

- ALL values are based on the Standard ambient Temperature 25°C and pressure 0.1Mpa.
- SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE
- Replacements for Manson Engineering SPS-5600 and SPS-5602 units!