



48V at 5A, 10A, 20A also available

Power Supply Features

- 3-phase, 340~550VAC wide range input (2-phase operation also possible)
- Built-in "active" PFC (except TDR-240 – "passive")
- High efficiency up to 94.5%
- Protection: Short circuit / Overload / Over voltage / Over temperature
- Cooling by free air convection
- Built-in constant current limiting circuit
- Can be installed on DIN rail TS-35/7.5 or 15
- UL508/UL61010-1 industrial control equipment approved
- Current sharing up to 3840W (3+1) for TDR-960
- Built-in DC OK relay contact (optional on TDR-480)
- 3 year warranty

General Specifications (Please refer to www.procontechology.com.au for detailed specs)


Model No.	TDR-240	TDR-480	TDR-960
AC input voltage range	3-phase 340~550VAC (2-phase operation possible); 480~780VDC		
AC input current	0.69A / 400VAC, 0.6A / 500VAC	0.85A / 400VAC, 0.7A / 500VAC	2.0A / 400VAC, 1.4A / 500VAC
AC inrush current (typ.)	Cold start, 50A		Cold start, 60A
DC adjustment range	24V: 24~28V, 48V: 48~55V		
Overload protection	105~130% rated output power, constant current limiting, unit will shut down after 3 sec., re-power on to recover 105~130% rated output power, constant current limiting, unit will hiccup after 3 sec. (TDR-240)		
Over voltage protection	Range	29~33V for 24V model, 56~65V for 48V model (30~36V for TDR-240-24)	
	Type	Shut down o/p voltage, re-power on to recover Hiccup mode, recovers automatically after temperature goes down	
Over temp. protection	Shut down output voltage, recovers automatically after temperature goes down		
Withstand voltage	I/P-O/P: 4.8kVAC, I/P-FG: 2.4kVAC, O/P-FG: 0.5kVAC, O/P-DC OK: 0.5kVAC	I/P-O/P: 3kVAC, I/P-FG: 2kVAC, O/P-FG: 0.5kVAC, O/P-DC OK: 0.5kVAC (TDR-960; optional for TDR-480)	
Isolation resistance	100MΩ (min.) @500VDC		
Working temperature	-30°C ~ +70°C (refer to output derating curve)		
DC OK signal	Relay Contact 30VDC 1A 30VAC 0.5A resistive load (optional for TDR-480)		
Leakage current	< 2mA at 530VAC	< 3.5mA at 530VAC	
Vibration	10~500Hz, 2G 10 minutes / 1 cycle, period of 60 minutes each a long X, Y, Z axes		
Safety standards	UL61010-1, UL61010-2-201, EAC TP TC 004, EN61558-2-16 approved	UL508, IEC62368-1, EAC TP TC 004 approved	
EMC standards	EN55032 class B, EN61000-3-2, 3, EN61000-4-2, 3, 4, 5, 6, 8, 11, EN61204-3, EN55024, EN61000-6-2, EAC TP TC 020, heavy industry level		
Connection	I/P: 4 poles, O/P: 4 poles screw DIN terminals		I/P: 4 poles, O/P: 6 poles
Dimensions (WxHxD)	63x125.2x113.5mm	85.5x125.2x128.5mm	110x125.2x150mm
Weight	1kg	1.51kg	2.47kg

TDR-240 Series



Model No.	Output	Tol.	R&N	Eff.
TDR-240-24	24V, 0~10A	±1.0%	100mV	92%
TDR-240-48	48V, 0~5A	±1.0%	120mV	92%

TDR-960 Series



Model No.	Output	Tol.	R&N	Eff.
TDR-960-24	24V, 0~40A	±1.0%	180mV	94.0%
TDR-960-48	48V, 0~20A	±1.0%	250mV	94.5%

TDR-480 Series



Model No.	Output	Tol.	R&N	Eff.
TDR-480-24	24V, 0~20A	±1.0%	150mV	92.5%
TDR-480-48	48V, 0~10A	±1.0%	150mV	93%

TDR vs. DRT

Series	Difference	Dimension (width)	Working Temp.
TDR		63~110mm by model	-30~+70°C
DRT		125.2~276mm by model	-20~+60°C/+70°C

Tol = voltage tolerance; R&N = Ripple & Noise (peak to peak); Eff = Efficiency